

Cellular Auto Dialer

CAD-03 Kit

The CAD-03 is a do-it-yourself security dialer that uses GSM cellular service to send a message when an alarm is generated. When an alarm is caused by one of the wireless sensors or tamper switch the dialer will call out and play one of two ten second messages that you record yourself. You can program up to nine different telephone numbers for the dialer to call. There is an entrance and exit delay as well as a local alarm. The dialer can be triggered by wireless PIR sensors, shock sensors or door contacts. The back-up battery allows the dialer to operate for 12 to 24 hours without AC power. The ruggedized construction and plastic carrying case mean that the CAD-03 can be used at construction sites, RVs, boats or other hard to monitor locations. The only thing you will need to add is an active GSM Sim card (AT&T, T-Mobile, etc.) The dialer will work anywhere you have GSM cell service making it ideal for remote locations or homes that do not have a land line telephone.

Kit includes: Cellular Auto Dialer; One wireless PIR sensor; One wireless shock sensor; AC power adaptor; Back-up battery pack; Hard-sided carry case.



Auto Dialer Accessories

AD-PIRW

The passive infrared (PIR) detector operates on a 9 volt battery and will detect motion to a distance of about 40' in front of the sensor. The PIR will then send a radio signal up to 200' back to the auto dialer.



AD-SSW

The wireless shock sensor can be placed in a trailer, truck, RV, etc. and will detect the movement caused by someone tampering with the vehicle. The sensor will then send a radio signal up to 200' back to the auto dialer.



AD-KFW

The wireless key fob can be used to arm and disarm the auto dialer from a distance of about 200'. The key fob can also be used as a panic alarm.



AD-DCW

The wireless door contact can be used to monitor doors or windows. The sensor will then send a radio signal up to 200' back to the auto dialer when a door or window is opened.