

# Sensaphone Accessory Guide

## IMS Sensors & Accessories

### Dual Relay Output Module



#### Description

The IMS-4310 Dual Relay Output Module allows you to control two devices from any IMS-4000 Host or Node. Each output may be controlled either manually or automatically. Each output has the option of providing either a dry relay contact or 12VDC power. Two switches located inside the device select the output type. Please read all of the instructions that follow for proper installation, wiring, and programming.

#### Specifications

**Temperature:**

32–122°F

**Humidity:**

5–90 %RH

**Number of Outputs:**

2

**Output Type:**

Dry Contact or 12V Switched

**Output Rating (12V DC Model):**

1.5 Amps total (both outputs combined)

**Output Rating (Dry Contact Mode):**

2 Amps @ 30VAC/VDC, max

**Power Supply:**

100-240VAC 50/60Hz 0.6A to 12VDC 2A Power Adapter.

**Dimensions:**

5.5"l x 3.75"w x 1.5"h

**Housing:**

White plastic

**Compatibility:**

IMS-4000, IMS-1000, and Nodes

*\*Specifications subject to change without notice*

#### Package Contents

- (1) Dual Relay Output Module
- (1) 12VDC Power Supply
- (1) Instruction Manual
- (1) Serial Cable

Manufacturer Part Number . . . . . IMS-4310

## SENSAPHONE®

901 Tryens Road  
Aston, PA 19014  
Ph: 610-558-2700  
F: 610-558-0222  
www.sensaphone.com

