

LunaSafe Setup Tips and Directions

Thank you for your recent purchase of the LunaSafe pool alarm. Each transmitter has a water switch on the front that will be triggered when it comes into contact with water. This can be triggered by the entire transmitter going into the water, or just by have something like a wet cloth or branch touch the pins on the front.

- The first step to using your new LunaSafe system is to charge the receiver.
- To charge the receiver you need to be using a 10W Qi charging pad. Anything else or less than 10W will not charge the receiver properly. You can use the supplied one or any other that you have at home.
- The charging pad should have a red light when it is plugged in without a receiver on it. When the receiver is placed standing up in the center of the pad the light on the pad should turn blue to indicate it is charging.
- The receiver does work while charging, so once it is on the charging pad you can turn it on and have the system functioning.
- When the receiver is on the charging pad ensure the charging light is lit, if this does not turn on the receiver is not charging. This will turn off when the battery is fully charged.
- To test the system dip the transmitter into a cup of water, make sure both pins on the front are in the water.
- After testing the system you will need to press the check mark button twice to get the receiver back to the normal mode. First press silences the alarm, the second shuts off the strobe light.
- Transmitters are meant to be worn on the wrist for children, not ankles. Putting it on the ankle could result in the system not working properly and not triggering alarms when it should.
- If you are getting false alarms on your system the first step would be to try pairing sensors to the receiver, this will minimize outside interference.
- To pair the transmitters you will need to hold the check button until the pairing light turns on, approx. 5 seconds. To clear any paired transmitters you will need to hold the check button until the pairing light turns off and blinks, approx. 15 seconds.
- If pairing does not work you would want to isolate sensors so you can see which one is causing the problem. This can be done by pairing all but one until you find the one causing the false alarms.

Thank you again for your purchase of your LunaSafe pool alarm. Please let us know if you have any additional questions, comments, or concerns and we would be happy to assist you. You can reach us by phone at 1-800-487-1363 or email at support@diycontrols.com with any questions or concerns.